



COMMON PIPE CONFIGURATIONS

Thread/Tooljoint	Tooljoint O.D. (in.)	Tooljoint I.D. (in.)	Pipe O.D. (in.)	Pipe Wall Thickness	Est. Joint Weight* (lbs)
2-3/8" API IF (NC26)	3 1/2	1 5/8	3 1/2	0.368	270
2-7/8" API IF (NC31)	4 1/2	2 1/8	4 1/2	0.337	330
3-1/2" API IF (NC38)	5 1/2	2 11/16	5 1/2	0.362	440
3-1/2" API Reg	4 1/2	1 1/2	4 1/2	0.337	330
4-1/2" API Reg	5 1/2	2 1/4	5 1/2	0.362	440
2-3/8" FEDP	3 1/8	1 3/8	2 3/8	0.254	130
2-7/8" FEDP	3 3/4	3 1/4	2 7/8	0.276	170
Mayhew Junior	2 3/4	1 1/4	2 3/8	0.190	100
Mayhew Junior	2 7/8	1 1/4	2 7/8	0.276	170
Mayhew Regular	3 1/4	1 1/2	2 3/8	0.254	130
Mayhew Regular	3 1/2	1 1/2	3 1/2	0.368	270
AW/AWJ	1 3/4	5/8	1 3/4	0.188	70
NW/NWJ	2 5/8	1 3/8	2 5/8	0.250	140
HELANBAK provides a variety of breakout configurations, wall thicknesses, and joint lengths to meet your specific rig needs.					

*Weights calculated on 20' joint lengths. Actual weight may vary upon joint length, breakouts, etc.